



### Corrugated Stainless Steel Flexible Water Softener Connectors Specification Sheet

#### SPECIFICATION:

Furnish and install Corrugated Stainless Steel  
Boiler or Softener Connector

#### DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

#### COMPLIANCES/LISTINGS:

- \* ICC-ES PMG
- \* ICC Listed, Tested & Certified
- \* UPC, IPC, IMC, IRC (USA)
- \* Low Lead Compliant California H & S Code 116875
- \* ASME A112.18.6/CSA B125.6-2009 Compliant
- \* NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)
- \* State of Wisconsin, Commonwealth of Massachusetts

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWC-112 x 18	1 1/2" FIP x 1 1/2" FIP	18"
SWC-112 x 24	1 1/2" FIP x 1 1/2" FIP	24"



#### Product Submittal

Job Name: \_\_\_\_\_

Date: \_\_\_\_\_

Model# \_\_\_\_\_ Quantity: \_\_\_\_\_

Architect/Contractor: \_\_\_\_\_

ANSI/NSF 61



Compliant to AB1953

ASME A112.18.6