



## Corrugated Stainless Steel Flexible Water Heater/Softener Connectors Specification Sheet

### SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

### DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- True 31/32" ID
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required!
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- **Dual Purpose Sweat Installation\***
- **Slip over copper pipe & sweat or**
- **Cut and insert into ball valve**
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

### COMPLIANCES/LISTINGS:

- \* ICC-ES PMG File #1077
- \* ICC Listed, Tested & Certified
- \* Complies with UPC, IPC, IMC, IRC, CSA
- \* Low Lead Compliant ICC File # 1078
- \* ASME A112.18.6 Compliant
- \* NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)
- \* State of Wisconsin, Commonwealth of Massachusetts

<u>Model #</u>	<u>Description</u>	<u>Length</u>
<b>SWT-1</b>	<b>1" Copper Swt x Fem</b>	<b>15,18,24"</b>
Swt x Fem-15	1" Swt x 1" FIP	15"
Swt x Fem-18	1" Swt x 1" FIP	18"
Swt x Fem-24	1" Swt x 1" FIP	24"

**\*Dual Purpose: slip onto copper pipe and sweat  
Or Cut @ bell and insert into ball valve!**



ANSI/NSF 61



Compliant to AB1953

ASME A112.18.6



### Product Submittal

Job Name: \_\_\_\_\_

Date: \_\_\_\_\_

Model# \_\_\_\_\_ Quantity: \_\_\_\_\_

Architect/Contractor: \_\_\_\_\_